



# DF115 A

## Specifications & Advantages

Engine Type	4 - Stroke DOHC 16 - Valve
Fuel Delivery System	Multi Point Sequential Electronic Fuel Injection
Transom Height mm (in.)	L: 508 (20) X: 635 (25)
Starting System	Electric
Dry Weight kg (lbs.):	L: 182.0 (401) X: 187.0 (412)
No. Of Cylinders	In line - 4
Piston Displacement cc (cu. in.)	2,044 (124.7)
Bore X Stroke Inches (mm)	86 x 88 (3.40 x 3.50)
Maximum Output Kw (HP) / RPM	84.6 (115)
Operating Range (RPM)	5600 - 6000
Steering	Remote (Tiller Kit Optional)
Oil Pan Capacity liters (U.S. / Imp qts.)	5.8 (5.5)
Ignition System	Fully-transistorized
Alternator	12V 40A
Trim Method	Power Trim and Tilt
Gear Ratio	2.59:1
Gear Shift	F-N-R (Electronic)
Exhaust	Through Prop Hub Exhaust
Propeller Selection (in.)	15 - 26

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

**FOR YOUR SAFETY:**

- Read your owner's manual carefully.
- Operate your outboard safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts