



DF150 AP

Specifications & Advantages

Engine Type	4 - Stroke DOHC 16 - Valve
Fuel Delivery System	Multi Point Sequential Electronic Fuel Injection
Transom Height mm (in.)	L: 508 (20) X: 635 (25)
Starting System	Electric
Dry Weight kg (lbs.):	L: 236 (520) X: 241(531)
	In line - 4
No. Of Cylinders	2,867 (174.9)
Piston Displacement cc (cu. in.)	97 X 97 (3.81 X 3.81)
Bore X Stroke Inches (mm)	110.0 (150)
Maximum Output Kw (HP) / RPM	5000 - 6000
Operating Range (RPM)	Remote
Steering	8.0 (8.5 / 7.0)
Oil Pan Capacity liters (U.S. / Imp qts.)	Fully-transistorized
Ignition System	12V 44A
Alternator	Power Trim and Tilt
Trim Method	2.50: 1
Gear Ratio	F-N-R (Electronic)
Gear Shift	Through Prop Hub Exhaust
Exhaust	17"-27"

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner's manual carefully.
- Operate your outboard safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts