



# DF90 A

## Specifications & Advantages

Engine Type	4 - Stroke DOHC 16 - Valve
Fuel Delivery System	Multi Point Sequential Electronic Fuel Injection
Transom Height mm (in.)	L: 510 (20) X: 637 (25)
Starting System	Electric
Dry Weight kg (lbs.):	L: 155 kg; 341 lbs / X: 158 kg; 348 lbs
No. Of Cylinders	In line - 4
Piston Displacement cc (cu. in.)	1502 (91.7)
Bore X Stroke Inches (mm)	75 x 85 (3.00 x 3.30)
Maximum Output Kw (HP) / RPM	66.2 (90)
Operating Range (RPM)	5300 - 6300
Steering	Remote (Tiller Kit Optional)
Oil Pan Capacity liters (U.S. / Imp qts.)	4.0 (4.2)
Ignition System	Fully-transistorized
Alternator	12V 27A
Trim Method	Power Trim and Tilt
Gear Ratio	2.59:1
Gear Shift	F-N-R (Electronic)
Exhaust	Through Prop Hub Exhaust
Propeller Selection (in.)	13 - 24

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

**FOR YOUR SAFETY:**

- Read your owner's manual carefully.
- Operate your outboard safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts