



DF2.5

Specifications & Advantages

Engine Type	4 – Stroke OHV 2-Valve
Fuel Delivery System	Carburetor
Transom Height mm (in.)	S: 381 (15)
Starting System	Manual
Dry Weight kg (lbs.)	S: 13 (29)
No. Of Cylinders	1
Piston Displacement cc (cu. in.)	68 (4.1)
Bore X Stroke mm (inches)	48 x 38 (1.89 x 1.50)
Maximum Output Kw (HP) / RPM	1.8 (2.5)
Operating Range (RPM)	5250 - 5750
Steering	Tiller
Oil Pan Capacity liters (U.S. qts.)	.3 (.32)
Ignition System	Digital CDI
Alternator	N/A
Trim Method	Manual 4 Tilt Pin Positions
Gear Ratio	2.15:1
Gear Shift	F-N-R
Exhaust	Above Prop Exhaust
Propeller Selection (Standard)	3 x 7.5 x 5.5
Fuel Tank Capacity	Integral 1L

Specifications, appearances, equipment, colors, materials and other items of “SUZUKI” products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner’s manual carefully.
- Operate your outboard safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts



DF2.5

Specifications & Advantages

Model Name:	DF2.5	2 Honda	2.5 Mercury	Yamaha 2.5
Manufacturer:	Suzuki	Honda	Mercury	Yamaha
Horsepower:	2.5	2	2.5	2.5
Shaft Length (Inches):	S(15)	S (15), L (20)	S (15)	S (15)
Weight (Lbs):	S (30.1)	S (27), L (20)	S (38)	S (37)
Cylinders:	1	1	1	1
Valves Per Cylinder:	2	2	2	2
Valve Train Drive:	Pushrod Cam	Pushrod Cam	Pushrod Cam	Pushrod Cam
Displacement:	4.2 cu. in. (68 cc)	3.4 cu. in. (57 cc)	5.2 cu. in. (85 cc)	4.4 cu. in. (72 cc)
Bore and Stroke (Inches/mm):	1.89 x 1.50 in. (48 x 38 mm)	1.8 x 1.4 in. (45 x 36 mm)	2.16 x 1.42 in. (53 x 36 mm)	2.13 x 1.24 in. (54 x 31.5 mm)
Operating Range (RPM):	5250-5750	5000 - 6000	5000 - 6000	5250 -5750
Induction System:	1 carb	1 carb	1 carb	1 carb
Starting System:	Manual start w/ manual choke	Manual	Manual	Manual
Lubrication:	Wet sump	Wet sump	Wet sump	Splash
Oil Tank Capacity:	0.32 qt. (0.3 lit.)	0.42 qt. (0.4 lit.)	Unknown	0.35 qt. (0.33 lit.)
Ignition:	Suzuki PEI	Transistorized	CDI	TCI
Trim Type:	4 positions	Unknown	4 positions	4 positions
Gear Ratio:	2.15:1	2.11:1	2.15:1	2.08:1 / 13:27
CARB Emissions Rating:	3-Star Ultra-Low	3-Star Ultra Low	3-Star Ultra Low	2-Star Very Low
Standard Propeller (Blades x Dia. x Pitches (Ins.)):	3 X 7½ X 5½	3 x 7¼ x 7½ plastic	Unknown	3 x 7¼ x 6
Steering:	360°, Tiller	360°	360°	360°

DF2.5 Advantages

Over Honda

- 4.2 cu. in. vs. 3.4 cu. in. No replacement for displacement.
- Water cooled vs. Air cooled
- .4 gal (1.5 lit) vs .26 (1 lit.) Integral tank holds more fuel so you can run farther.

Over Mercury

- 30 lbs. vs. 38lbs. Lightweight, compact design, better power to weight ratio.

Over Yamaha

- 30 lbs. vs. 37lbs. Lightweight, compact design, better power to weight ratio.
- .4 gal (1.5 lit) vs .26 (1 lit.) Integral tank holds more fuel so you can run farther.
- 3 Star vs. 2 Star