

DF6 A

Specifications & Advantages

Engine Type	4 - Stroke OHV 2-Valve
Fuel Delivery System	Carburetor
Transom Height mm (in.)	S: 381 (15); L: 508(20)
Starting System	Manual
Dry Weight kg (lbs.):	S: 24 L: 25
No. Of Cylinders	1
Piston Displacement cc (cu. in.)	138 (8.4)
Bore X Stroke Inches (mm)	60.4X48
Maximum Output Kw (HP) / RPM	4.4 (6)
Operating Range (RPM)	4750 - 5750
Steering	Tiller
Oil Pan Capacity liters (U.S. / Imp qts.)	.7 (.74)
Ignition System	Digital CDI
Alternator	12V 6A (Optional)
Trim Method	Manual 5 Tilt Pin Positions
Gear Ratio	1.92:1
Gear Shift	F-N-R
Exhaust	Above Prop Exhaust
Propeller Selection (in.)	6 - 7
Fuel Tank Capacity	Integral 1L

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner's manual carefully.
- Operate your outboard safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts