



DF9.9B

Specifications & Advantages

Engine Type	4 – Stroke SOHC 4-Valve
Fuel Delivery System	Electronic Fuel Injection with Lean Burn
Transom Height mm (in.)	L:20" X: 25"
Starting System	Electric: L and X
Dry Weight kg (lbs.)	Electric L: 108 X: 120
No. Of Cylinders	In line - 2
Piston Displacement cc (cu. in.)	20.0 (327)
Bore X Stroke mm (inches)	2.38 x 2.24 (60.4 x 57)
Maximum Output Kw (HP) / RPM	9.9
Operating Range (RPM)	4700 - 5700
Steering	Remote: L:Remote X: Remote
Oil Pan Capacity liters (U.S. qts.)	1.06 (1.0)
Ignition System	Digital CDI
Alternator	12V 12A (Optional)
Trim Method	5 Tilt Pin Positions and 2 Shallow Water Drive Settings / Optional Power Tilt model
Gear Ratio	2.08:1
Gear Shift	F-N-R
Exhaust	Through Prop Hub Exhaust
Propeller Selection (in.)	7 - 11
Fuel Tank Capacity	Separate 12L

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice. Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner's manual carefully.
- Operate your outboard safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Part