

2015 King Quad / LT-A400F

SPECIFICATIONS

| Engine: | 376cc, 4-stroke, Air-cooled with SACS, single cylinder, OHC |
|---------------------|---|
| Bore Stroke: | 82.0 mm (3.228 in) x 71.2 mm (2.803 in) |
| Compression Ratio: | 9.0 : 1 |
| Fuel System: | KEIHIN CVK32, single |
| Lubrication: | Wet sump |
| Ignition: | Electronic ignition (CDI) |
| Transmission: | Automatic variable ratio (V-belt) |
| Final Drive: | Shaft drive |
| Overall Length: | 2060 mm (81.1 in) |
| Overall Width: | 1145 mm (45.1 in) |
| Overall Height: | 1220 mm (48.0 in) |
| Seat Height: | 840 mm (33.1 in) |
| Ground Clearance: | 250 mm (9.8 in) |
| Wheelbase: | 1270 mm (50.0 in) |
| Curb Weight: | 285 kg (628 lbs) |
| Suspension Front: | Independent, double wishbone, coil spring, oil damped |
| Suspension Rear: | Swingarm type, coil spring, oil damped |
| Brakes Front: | Disc brake, twin |
| Brakes Rear: | Drum brake |
| Tires Front: | AT25 x 8-12, tubeless |
| Tires Rear: | AT25 x 10-12, tubeless |
| Fuel Tank Capacity: | 16.0 L (4.2/3.5US/Imp gal) - Including Reserve |
| Color: | Terra Green and Flame Red |

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- The LT-A400F is for use only by those aged 16 and older.
- Read your owner's manual carefully.
- Follow all scheduled maintenance as recommended.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- ATVs can be hazardous to operate.
- Always avoid paved surfaces. Never ride on public roads.
- Never carry passengers or engage in stunt riding.
- Avoid excessive speed. Be extra careful on difficult terrain.