



## ***Boulevard C90BT***

<b>Engine:</b>	1462cc, 4-stroke, 2-cylinder, Liquid-cooled, SOHC, 54-degree V-twin
<b>Bore Stroke:</b>	96.0 mm x 101.0 mm (3.78 in x 3.98 in )
<b>Compression Ratio:</b>	9.5 : 1
<b>Fuel System:</b>	Suzuki Fuel Injection
<b>Lubrication:</b>	Wet sump
<b>Ignition:</b>	Electronic ignition (Transistorized)
<b>Transmission:</b>	5-speed constant mesh
<b>Final Drive:</b>	Shaft Drive
<b>Overall Length:</b>	2560 mm (100.8in)
<b>Overall Width:</b>	990 mm (39.0 in)
<b>Overall Height:</b>	1440 mm (56.7 in)
<b>Seat Height:</b>	720 mm (28.3 in)
<b>Ground Clearance:</b>	140 mm (5.5 in)
<b>Wheelbase:</b>	1675 mm (65.9 in)
<b>Curb Weight:</b>	363 kg (800 lbs)
<b>Suspension Front:</b>	Telescopic, coil spring, oil damped
<b>Suspension Rear:</b>	Link type, coil spring, oil damped
<b>Brakes Front:</b>	Disc brake
<b>Brakes Rear:</b>	Drum brake
<b>Tires Front:</b>	130/80-17M/C 65H, tubeless
<b>Tires Rear:</b>	200/60-16M/C 79H, tubeless
<b>Fuel Tank Capacity:</b>	18.0 L (4.8/4.0 US/Imp gal)
<b>Color:</b>	Glass Sparkle Black

Specifications, appearances, equipment, colors, materials and other items of “SUZUKI” products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

### **FOR YOUR SAFETY:**

- Read your owner’s manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts