

2018 / DR200S

SPECIFICATIONS

| Engine: | 199 cc (12.1 cu. in), 4-stroke, air-cooled, OHC |
|---------------------|---|
| Bore Stroke: | 66.0 mm x 58.2 mm (2.60 in x 2.29 in) |
| Compression Ratio: | 9.4 : 1 |
| Fuel System: | MIKUNI BST31SS, single |
| Lubrication: | Wet sump |
| Ignition: | Electronic ignition (CDI) |
| Transmission: | 5-speed constant mesh |
| Final Drive: | Chain, DID525V9, 110 links |
| Overall Length: | 2155 mm (84.8 in) |
| Overall Width: | 805 mm (31.7 in) |
| Overall Height: | 1140 mm (44.9 in) |
| Seat Height: | 845 mm (33.3 in) |
| Ground Clearance: | 255 mm (10.0 in) |
| Wheelbase: | 1405 mm (55.3 in) |
| Curb Weight: | 126 kg (278 lbs) |
| Suspension Front: | Telescopic, coil spring, oil damped |
| Suspension Rear: | Link type, coil spring, oil damped |
| Brakes Front: | Disc brake |
| Brakes Rear: | Drum brake |
| Tires Front: | 70/100-21M/C 44P tube type |
| Tires Rear: | 100/90-18M/C 56P tube type |
| Fuel Tank Capacity: | 13.0 L (3.4 US gallons) |
| Color: | Champion Yellow No. 2 / Solid Special White No. 2 |

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner's manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts