

DR650E

SPECIFICATIONS

Engine:	644 cc (39.3 cu. in), 4-stroke, air-cooled, OHC
Bore Stroke:	100 mm (3.937 in) x 82 mm (3.228 in)
Compression Ratio:	9.5 : 1
Fuel System:	MIKUNI BST40, single
Lubrication:	Wet sump
Ignition:	Electronic ignition (CDI)
Transmission:	5-speed constant mesh
Final Drive:	Chain, DID525V9, 110 links
Overall Length:	2255 mm (88.8 in),
Overall Width:	865 mm (34.1 in)
Overall Height:	1195 mm (47.0 in),
Seat Height:	885 mm (34.8 in), Low seat 845 mm (33.0 in.)
Ground Clearance:	265 mm (10.4 in),
Wheelbase:	1490 mm (58.7 in),
Curb Weight:	166 kg (366 lbs)
Suspension Front:	Telescopic, coil spring, oil damped
Suspension Rear:	Link type, coil spring, oil damped
Brakes Front:	Disc brake, single floating rotor
Brakes Rear:	Drum brake, single rotor
Tires Front:	90/90-21M/C 54S, tube type
Tires Rear:	120/90-17M/C 64S, tube type
Fuel Tank Capacity:	13.0 L (3.4/2.9 US/Imp gal) - Including Reserve
Color:	Solid Special White No. 2

Specifications, appearances, equipment, colors, materials and other items of “SUZUKI” products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner’s manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts