

# DR650E

## SPECIFICATIONS

<b>Engine:</b>	644 cc (39.3 cu. in), 4-stroke, air-cooled, OHC
<b>Bore Stroke:</b>	100 mm (3.937 in) x 82 mm (3.228 in)
<b>Compression Ratio:</b>	9.5 : 1
<b>Fuel System:</b>	MIKUNI BST40, single
<b>Lubrication:</b>	Wet sump
<b>Ignition:</b>	Electronic ignition (CDI)
<b>Transmission:</b>	5-speed constant mesh
<b>Final Drive:</b>	D.I.D 525 V9, 110 links
<b>Overall Length:</b>	2255 mm (88.8 in),
<b>Overall Width:</b>	865 mm (34.1 in)
<b>Overall Height:</b>	1195 mm (47.0 in),
<b>Seat Height:</b>	885 mm (34.8 in), Low seat 845 mm (33.0 in.)
<b>Ground Clearance:</b>	265 mm (10.4 in),
<b>Wheelbase:</b>	1490 mm (58.7 in),
<b>Curb Weight:</b>	166 kg (366 lbs)
<b>Suspension Front:</b>	Telescopic, coil spring, oil damped
<b>Suspension Rear:</b>	Link type, coil spring, oil damped
<b>Brakes Front:</b>	Disc brake
<b>Brakes Rear:</b>	Disc brake
<b>Tires Front:</b>	90/90-21M/C 54S, tube type
<b>Tires Rear:</b>	120/90-17M/C 64S, tube type
<b>Fuel Tank Capacity:</b>	13.0 L (3.4/2.9 US/Imp gal) - Including Reserve
<b>Color:</b>	Solid Iron Gray

Specifications, appearances, equipment, colors, materials and other items of “SUZUKI” products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

### FOR YOUR SAFETY:

- Read your owner’s manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts