



# 2015 / RM-Z250

## SPECIFICATIONS

<b>Engine:</b>	249cc, 4-stroke, liquid-cooled, single cylinder, DOHC
<b>Bore Stroke:</b>	77.0mm (3.0 in) x 53.6mm (2.1 in)
<b>Compression Ratio:</b>	13.5:1
<b>Fuel System:</b>	Suzuki Fuel Injection
<b>Lubrication:</b>	Semi-dry sump
<b>Ignition:</b>	Electronic ignition (CDI)
<b>Transmission:</b>	5-speed constant mesh
<b>Final Drive:</b>	Chain, DID520DMA4, 114 links
<b>Overall Length:</b>	2170 mm (85.4 in)
<b>Overall Width:</b>	830 mm (32.7 in)
<b>Overall Height:</b>	1270 mm (50.0 in)
<b>Seat Height:</b>	955 mm (37.6 in)
<b>Ground Clearance:</b>	345 mm (13.6 in)
<b>Wheelbase:</b>	1475 mm (58.1 in)
<b>Curb Weight:</b>	106.5 kg (235 lbs)
<b>Suspension Front:</b>	Inverted telescopic, air spring, oil damped
<b>Suspension Rear:</b>	Link type, coil spring, oil damped
<b>Brakes Front:</b>	Disc brake
<b>Brakes Rear:</b>	Disc brake
<b>Tires Front:</b>	80/100-21 51M, tube type
<b>Tires Rear:</b>	100/90-19 57M, tube type
<b>Fuel Tank Capacity:</b>	6.5 L (1.7 US gallons)
<b>Color:</b>	Champion Yellow / Solid Black

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

### FOR YOUR SAFETY:

- Read your owner's manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- The RM-Z series motorcycles are for closed-course competition use and related practices only.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts