

## 2018 / RM-Z450

### SPECIFICATIONS

<b>Engine:</b>	449cc, 4-stroke, liquid-cooled, single cylinder, DOHC
<b>Bore Stroke:</b>	96.0mm (3.78 in) x 62.1mm (2.4 in)
<b>Compression Ratio:</b>	12.5:1
<b>Fuel System:</b>	Fuel Injection, 44 mm throttle body
<b>Lubrication:</b>	Semi-dry sump
<b>Ignition:</b>	Electronic ignition (CDI)
<b>Transmission:</b>	5-speed constant mesh
<b>Final Drive:</b>	Chain, DID520MXV4, 114 links
<b>Overall Length:</b>	2175 mm (85.6 in.)
<b>Overall Width:</b>	835 mm (32.9 in.)
<b>Overall Height:</b>	1260 mm (49.6 in.)
<b>Seat Height:</b>	960 mm (37.8 in.)
<b>Ground Clearance:</b>	330 mm (13.0 in.)
<b>Wheelbase:</b>	1495 mm (58.9 in)
<b>Curb Weight:</b>	112 kg (247 lbs)
<b>Suspension Front:</b>	Inverted telescopic, coil spring, oil damped, adjustable damping force
<b>Suspension Rear:</b>	BFRC - link type, coil spring, oil damped, adjustable spring preload & damping force
<b>Brakes Front:</b>	Disc brake, single rotor
<b>Brakes Rear:</b>	Disc brake, single rotor
<b>Tires Front:</b>	80/100-21 51M, tube type
<b>Tires Rear:</b>	110/90-19 62M, tube type
<b>Fuel Tank Capacity:</b>	6.3 L (1.6 US gallons)
<b>Color:</b>	Championship Yellow with black/blue accents

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

#### FOR YOUR SAFETY:

- Read your owner's manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- The RM-Z series motorcycles are for closed-course competition use and related practices only.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts