

AN650A / BURGMAN

SPECIFICATIONS

Engine:	638cc, 4-stroke, liquid-cooled, 2-cylinder, DOHC
Bore Stroke:	75.5mm x 71.3mm (2.97 in x 2.81 in)
Compression Ratio:	11.2 : 1
Fuel System:	Suzuki Fuel Injection
Lubrication:	Wet sump
Ignition:	Electronic ignition (Transistorized)
Transmission:	Automatic - SECVT
Final Drive:	Gear Drive
Overall Length:	2265 mm (89.2 in)
Overall Width:	810 mm (31.9 in)
Seat Height:	755 mm (29.7 in)
Ground Clearance:	125 mm (4.9 in)
Wheelbase:	1585 mm (62.4 in)
Curb Weight:	278 kg (613 lbs)
Suspension Front:	Telescopic, coil spring, oil damped
Suspension Rear:	Swingarm type, coil spring, oil damped
Brakes Front:	Disc brake, twin
Brakes Rear:	Disc brake
Tires Front:	120/70R15M/C 56H, tubeless
Tires Rear:	160/60R14M/C 65H, tubeless
Fuel Tank Capacity:	16.0 L (4.0 US gal)
Color:	Metallic Mat Fibroin Gray

Specifications, appearances, equipment, colors, materials and other items of “SUZUKI” products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner’s manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts