

# UH200A / BURGMAN

## SPECIFICATIONS

<b>Engine:</b>	200cc, 4-stroke, liquid-cooled, single-cylinder, OHC
<b>Bore Stroke:</b>	63.0 mm x 53.4 mm (2.717 in x 2.102 in)
<b>Compression Ratio:</b>	11.0 : 1
<b>Fuel System:</b>	Suzuki Fuel Injection
<b>Lubrication:</b>	Wet sump
<b>Ignition:</b>	Electronic ignition (Transistorized)
<b>Transmission:</b>	Automatic
<b>Final Drive:</b>	V-belt Drive
<b>Overall Length:</b>	2055 mm (80.9 in)
<b>Overall Width:</b>	740 mm (29.1 in)
<b>Seat Height:</b>	735 mm (28.9 in)
<b>Ground Clearance:</b>	130 mm (5.1 in)
<b>Wheelbase:</b>	1465 mm (57.7 in)
<b>Curb Weight:</b>	163 kg (359 lbs.)
<b>Suspension Front:</b>	Telescopic, coil spring, oil damped
<b>Suspension Rear:</b>	Swingarm type, coil spring, oil damped
<b>Brakes Front:</b>	Disc brake
<b>Brakes Rear:</b>	Disc brake
<b>Tires Front:</b>	110/90-13 M/C 56P, tubeless
<b>Tires Rear:</b>	130/70-12 62P, tubeless
<b>Fuel Tank Capacity:</b>	2.8 US - Including Reserve
<b>Color:</b>	Metallic Matte Titanium Silver

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

### FOR YOUR SAFETY:

- Read your owner's manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts