

GSX-R1000

SPECIFICATIONS

Engine:	999 cc, 4-stroke, 4-cylinder, liquid-cooled, DOHC
Bore Stroke:	74.5 mm x 57.3 mm
Compression Ratio:	12.8 : 1
Fuel System:	Fuel Injection
Lubrication:	Wet sump
Ignition:	Electronic ignition (Transistorized)
Transmission:	6-speed, constant mesh
Final Drive:	Chain, DID50VAZ, 114 links
Overall Length:	2045 mm (80.5 in.)
Overall Width:	710 mm (28.0 in.)
Overall Height:	1130 mm (44.5 in.)
Seat Height:	810 mm (31.9 in.)
Ground Clearance:	N/A
Wheelbase:	1405mm (55.3 in.)
Curb Weight:	203kg (448 lbs.)
Suspension Front:	Inverted telescopic, coil spring, spring preload fully adjustable, rebound and compression damping force fully adjustable
Suspension Rear:	Link type, oil damped, coil spring, spring preload fully adjustable, rebound and compression damping force fully adjustable
Brakes Front:	Radial mount, 4-piston calipers, 310 mm disc, twin
Brakes Rear:	1-piston caliper, 220 mm disc
Tires Front:	120/70ZR17M/C (58W), tubeless
Tires Rear:	190/50ZR17M/C (73W), tubeless
Fuel Tank Capacity:	17.5 L (4.6 US gal)
Color:	Metallic Triton Blue / Pearl Glacier White, Glass Sparkle Black / Metallic Mat Fibroin Gray

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner's manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts