

GSX-R600

SPECIFICATIONS

Engine:	599 cc, 4-stroke, 4-cylinder, liquid-cooled, DOHC
Bore Stroke:	67.0 mm x 42.5 mm (2.638 in x 1.673 in)
Compression Ratio:	12.9 : 1
Fuel System:	Fuel Injection
Lubrication:	Wet sump
Ignition:	Electronic ignition (Transistorized)
Transmission:	6-speed, constant mesh
Final Drive:	Chain, RK525SMOZ8, 114 links
Overall Length:	2030 mm (79.9 in)
Overall Width:	710 mm (28.0 in)
Overall Height:	1125 mm (44.3 in.)
Seat Height:	810 mm (31.9 in.)
Ground Clearance:	130mm (5.1in.)
Wheelbase:	1385 mm (54.5 in)
Curb Weight:	187 kg (412 lbs)
Suspension Front:	Inverted telescopic, coil spring, oil-damped
Suspension Rear:	Link type, oil damped, coil spring,
Brakes Front:	Brembo 4-piston, Disc, twin
Brakes Rear:	Nissin, 1-piston, Disc single
Tires Front:	120/70ZR17M/C (58W), tubeless
Tires Rear:	180/55ZR17M/C (73W), tubeless
Fuel Tank Capacity:	17.0 L (4.5 US gallons)
Color:	Metallic Triton Blue, Glass Sparkle Black / Marble Daytona Yellow, Metallic Matte Black No. 2 / Glass Sparkle Black

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner's manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts