

GSX-R600

SPECIFICATIONS

Engine:	599 cc, 4-stroke, 4-cylinder, liquid-cooled, DOHC
Bore Stroke:	67.0 mm x 42.5 mm
Compression Ratio:	12.8 : 1
Fuel System:	Fuel Injection
Lubrication:	Wet sump
Ignition:	Electronic ignition (Transistorized)
Transmission:	6-speed, constant mesh
Final Drive:	RK525SMOZ8, 114 links, Chain
Overall Length:	2040 mm (80.3 in.)
Overall Width:	715 mm (28.1 in.)
Overall Height:	1125 mm (44.3 in.)
Seat Height:	810 mm (31.9 in.)
Ground Clearance:	130mm (5.1in.)
Wheelbase:	1400mm (55.1 in.)
Curb Weight:	196kg (432 lbs.)
Suspension Front:	Inverted telescopic, coil spring, oil-damped
Suspension Rear:	Link type, oil damped, coil spring,
Brakes Front:	Radial mount, 4-piston calipers, 310 mm disc, twin
Brakes Rear:	1-piston caliper, 220 mm disc
Tires Front:	120/70ZR17M/C (58W), tubeless
Tires Rear:	180/55ZR17M/C (73W), tubeless
Fuel Tank Capacity:	16.0 L (4.2 US gal)
Color:	Metallic Triton Blue / Pearl Glacier White, Pearl Bracing White / Glass Sparkle Black

Specifications, appearances, equipment, colors, materials and other items of “SUZUKI” products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner’s manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts