

# GSX-R750

## SPECIFICATIONS

<b>Engine:</b>	750 cc, 4-stroke, 4-cylinder, liquid-cooled, DOHC
<b>Bore Stroke:</b>	70.0 mm x 48.7 mm
<b>Compression Ratio:</b>	12.5 : 1
<b>Fuel System:</b>	Fuel Injection
<b>Lubrication:</b>	Wet sump
<b>Ignition:</b>	Electronic ignition (Transistorized)
<b>Transmission:</b>	6-speed, constant mesh
<b>Final Drive:</b>	RK525ROZ5Y, 116 links, Chain
<b>Overall Length:</b>	2040 mm (80.3 in.)
<b>Overall Width:</b>	715 mm (28.1 in.)
<b>Overall Height:</b>	1125 mm (44.3 in.)
<b>Seat Height:</b>	810 mm (31.9 in.)
<b>Ground Clearance:</b>	130mm (5.1in.)
<b>Wheelbase:</b>	1400mm (55.1 in.)
<b>Curb Weight:</b>	198kg (437 lbs.)
<b>Suspension Front:</b>	Inverted telescopic, coil spring, oil-damped
<b>Suspension Rear:</b>	Link type, oil damped, coil spring,
<b>Brakes Front:</b>	Radial mount, 4-piston calipers, 310 mm disc, twin
<b>Brakes Rear:</b>	1-piston caliper, 220 mm disc
<b>Tires Front:</b>	120/70ZR17M/C (58W), tubeless
<b>Tires Rear:</b>	180/55ZR17M/C (73W), tubeless
<b>Fuel Tank Capacity:</b>	16.0 L (4.2 US gal)
<b>Color:</b>	Metallic Triton Blue / Pearl Glacier White, Glass Sparkle Black / Pearl Mira Red

Specifications, appearances, equipment, colors, materials and other items of “SUZUKI” products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

### FOR YOUR SAFETY:

- Read your owner’s manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts