Economically priced, high quality instruments feature easy plug-in wiring connections, perimeter-lighted dial, chrome bezels, contoured pointers and fog resistant glass lenses, All use standard 2" or 4" diameters for easy dash installation.





7,000 max RPM Tachs are available with or without 4-Stroke monitor functions. Monitor functions include: Low Oil Pressure Warning, Engine Temperature Warning, Check Engine Warning and Over-Rev Limit Warning.



Trolling Mode Control Switch

Allows the use of the Suzuki Troll Mode on equipped engines. When Troll mode is engaged, this switch allows for adjustments of engine RPM in 50 RPM increments, from idle to 1.200 RPM to make setting and maintaining a trolling speed easy. Consuk owner's manual or Suzuki Outboard Dealer for additional details on Suzuki Troll System operation

4" Tachometer With Suzuki Troll Mode Scale

A" TeChometer With Suzuki Trol Mode Scale
Easy to read 4" Tachometer has a scale from 0-7,000 RPM for standard use and a
secondary scale from 0-3,000 RPM with markers at 50 RPM intervals for use with the
Suzuki Troll Mode System. Gauge also includes warning lamps for fingine Temperature,
Low Oil, Check Engine, and Over-Rev When in Troll mode, Over-Rev Lamp stays on to
indicate that Troll mode has been engaged. The secondary RPM scale is designed to
make setting and manitaning a lower troll speed single. Fins FIA4A,50A,50A,WISOM/SOA/
OAV/TOA/90A115A/140A (1930 requires C-10 gauges) "See engine owner's manual
for information about Sizuki Iroll Mode system. Not all mode is come equipped with
trolling mode system. Accessory Iroll Mode Switch is required for Suzuki Iroll Mode
System use. Suzuki recommends the use of this Suzuke for trolling use.

34200-93151

DF40A5CA/SOA/YGA/SOA/YGA/SOA/YGA/SOA/15A/140A/150/175/250SS

(DF150/175AP/200AP/25OAP/300A/Y300 requires digital instrumentation)



4" Speedometers

Bourdon-tube type speedometer with readings in M.P.H. and Km/h. Includes viryl tube, plus all installation instructions and hardware. "Pitot tube 34190-87D00 must be ordered separately.

34100-93J11 80 mph 34100-93J31 50 mph 34190-87D00* Pitot Tut







2" Hour Meter

12 volt electric motor driven meter indicates the number of hours your outboard motor has been operated to indicate when periodic services are necessary

34500-93J11 White



2" Trim Guage

Magnetic type gauge shows trim angle for optimum performance and effeciency

34800-93J11 White



2" Voltmeter A well charged battery is essential for quick and easy starts. Monitor the charging system using a Voltmeter.

34600-93J11 White



2" Fuel Gauge

Operates on 12 volts with magnetically damped needle. Works with most fuel tank sending units.

34300-93J11 White



2" Water Pressure Gauge 15 psi

Bourdon-tube type gauge measures cooling water pressure. Instructions and dash installation hardware included. Order Installation kit for appropriate model. 34650-93J31 White



DF225/250/2508/300AP DF225/250/2508/300AP DF150/150AP/30AP DF150/150AP/350AP DF150/150AP/350AP DF150/150AP/350AP 34660-99E00 DF60/70 DF40/50 34660-97J00 DF40/50 34660-90J02 DF40/50 DF40/50 DF40A/50A/50AV/60A/60AV/70A/90/ DF90A/115/115A/140/140A

Economically priced, high quality instruments feature easy plug-in wiring connections, perimeter-lighted dial, chrome 40 45 bezels, contoured pointers and 35 SUZUKI 50 fog resistant glass lenses, All use standard 2" or 4" diameters for easy dash installation. 20

MPH

4" Speedometer

Easy to read 4" Speedometer features include lighted dial, contoured pointer and fog resistant glass lens,
*Requires Tubing 99105–80009.

99105-80102 White 60 mph 99105-80009* Speedometer Tubing (not shown)



4" Tachometers

7,000 max RPM Terbis are available with or without 4-Stroke monitor functions. Monitor functions include: Low oil Pressure Warning, Engine Temperature Warning, Check Engine Warning and Over-Petr Limit Warning.
99105-80101 White – With monitor functions
99105-80100 White – Without monitor functions



SUZUKI

2" Engine Monitor Gauge

Engine Monitor Gauge for 4-stroke engines helps alert you to low oil pressure, high engine temperature and engine over-rev.

99105-80108 White



2" Hour Gauge

Handy Hour Meter helps you keep track of the time between services and total running time.

99105-80107 White



2" Voltmeter

A well charged battery is essential for quick and easy starts. Monitor the charging system using a Voltmeter.

99105-80106 White





2" Trim Gauge

To help maintain steering stability and good performance, proper trim angle is essential. The Trim Gauge helps you monitor the trim angle. For use with 2-wire senders.

99105-80105 White



2" Fuel Gauge

Adding a Fuel Gauge can help you monitor fuel level. Connects easily using your boat's fuel sending unit harness.

99105-80103 White



2" Water Pressure Gauge 30 psi

Bourdon-tube type gauge measures cooling water pressure. Instructions and dash installation hardware included. Order Installation kit for appropriate model.

99105-80104 White

Water Pressure Gauge Installation Kits

34660-93J00	DF225/250/250AP/300AP	34660-87J00	DF40/50
34660-96J00	DF150/150AP/150A/DF175/175AP/175A/200A	34660-99E00	DF60/70
34660-90102 DE404/504/504//604/604//704/904/90/115/1154/140/1404			



Suzuki Genuine Instruments are custom-designed to provide the quality, reliability and value you expect from Suzuki Products. The wide selection allows you to accurately monitor a variety of essential functions. All instruments are lighted for night time boating and feature standard 2" and 4" diameters for easy installation.





7,000 max RPM Tachs are available with or without 4-Stroke monitor functions, Monitor functions include: Low Oil Pressure Warning, Engine Temperature Warning, Check Engine Warning and Over-Rev Limit Warning.

34200-93J00 with monitor functions 34200-93J20 without monitor





Trolling Mode Control Switch

Allows the use of the Suzuki Troll Mode on equipped engines. When Troll mode is engaged, this switch allows for adjustments of engine BPM in 50 RPM increments, from lide to 1,200 PPM to make setting and maintainiary a trolling speed easy. Corsult owner's manual or Suzuki Outboard Dealer for additional details on Suzuki Troll System operation



4" Tachometer With Suzuki Trol Mode Scale

4" Tachometer With Suzuki Tro! Mode Scale
Easy to read 5" Tachometer has a seale from 0-7,000 RPM for standard use, and a
secondary scale from 0-3,000 RPM with markers at 50 RPM internal for use with
the Suzuki Tro! Mode System." Gauge also includes variening lamps for Engine
Temperature, Low Oil, Check Engine and Over-Rev. When in troil mode, Over-Rev lamp
stays onto indicate that Troil mode has been negaged. The secondary RPM scale is
designed to make setting and marketing a joiner troil speed single. "See setting and marketing a joiner troil speed single." See engine
owner's namula for information about Suzuki Troil Mode system. Into all models comcupinged with Intoling mode system. Accessory final flood Switch required for Suzuki
Troil Mode System use. Suzuki recommend the use of This gauge for troiling use.
34200–33140
DF404/SADSOM/ROAGOM/ROAGOM/ROAGOM/SADOM/SADISIA/TAGIS/TS/SSOSS
(DF150/175AP/200AP/250AP/300AP/300 requires digital instrumentation)



4" Speedometers

Bourdon-tube type speedometer with readings in M.P.H. and Km/h. Includes viryl tube, plus all installation instructions and hardware. "Pitot tube 34190-87D00 must be ordered separately.

34100-93J00 80 mph 34100-93J20 50 mph 34190-87D00* Pitot Tub





2" Hour Meter

12 volt electric motor driven meter indicates the number of hours your outboard motor has been operated to indicate when periodic services are necessary.

34500-93J00 Black



2" Trim Meter

Magnetic type gauge shows trim angle for optimum performance and efficiency.

34800-93J00 Black



2" Voltmeter

A well charged battery is essential for quick and easy starts. Monitor the charging system using a Voltmeter.

34600-93J00 Black



2" Fuel Gauge

Operates on 12 volts with magnetically damped needle. Works with most fuel tank sending units.

34300-93J00 Black



2" Water Pressure Gauge 15 psi


Bourdon-tube type gauge measures cooling water pressure. Instructions and dash installation hardware included. Order Installation kit for appropriate model. 34650-93J20 Black

Kit includes fittings and hoses needed for motor t gauge connection.					
34660-93J00	DF225/250/250AP/300APP				
34660-96J00	DF150/150AP/150A/				
	DF175/175AP/175A/200A				
34660-99E00	DF60/70				
34660-87J00	DF40/50				
34660-90J02	DF40A/50A/50AV/60A/60AV/70A/90/				
	DF90A/115/115A/140/140A				

30 40

RPM × 100

SUZUKI



4" Speedometer

Easy to read 4° Speedometer features include lighted dial, contoured pointer and fog resistant glass lens. *Requires Tubing 99105-80009.

99105-80002 Black 60 mph 99105-80009* Speedometer Tubing (not shown)



4" Tachometers

7,000 max RPM Tachs are available with or without 4-Stroke monitor functions. Monitor functions include: Low Oil Pressure Warning, Engine Temperature Warning, Check Engine Warning and Over-Rev Limit Warning.

99105-80001	Black - With monitor functions
99105-80000	Black - Without monitor functions



2" Engine Monitor Gauge

Engine Monitor Gauge for 4–stroke engines helps alert you to low oil pressure, high engine temperature and engine over-rev.

99105-80008 Black



2" Hour Gauge

Handy Hour Meter helps you keep track of the time between services and total running time.

99105-80007 Black



2" Voltmeter

A well charged battery is essential for quick and easy starts. Monitor the charging system using a Voltmeter.

99105-80006 Black





2" Trim Gauge

To help maintain steering stability and good performance, proper trim angle is essential. The Trim Gauge helps you monitor the trim angle. For use with 2-wire senders.

99105-80005 Black



2" Fuel Gauge

Adding a Fuel Gauge can help you monitor fuel level. Connects easily using your boat's fuel sending unit harness.



2" Water Pressure Gauge 30 psi

Bourdon-tube type gauge measures cooling water pressure. Instructions and dash installation hardware included. Order Installation kit for appropriate model.

99105-80004 Black

Water Pressure Gauge Installation Kits

34660-93J00	DF225/250/250AP/300AP	34660-87J00	DF40/50	
34660-96J00	DF150/150AP/150A/DF175/175AP/175A/200A	34660-99E00	DF60/70	
34660-90J02	DF40A/50A/50AV/60A/60AV/70A/90A/90/115/115A/140/140A			