

# DF30 A

## Specifications & Advantages

Engine Type	4 – Stroke SOHC 4-Valve
Fuel Delivery System	Electronic Fuel Injection with Lean Burn
Transom Height mm (in.)	S: 381 (15) L:508(20)
Starting System	Electric or Manual
Dry Weight kg (lbs.):	65 (143)
No. Of Cylinders	In line -3
Piston Displacement cc (cu. in.)	490 (29.90)
Bore X Stroke Inches (mm)	60.4 x 57 (2.80 x 2.68)
Maximum Output Kw (HP) / RPM	22.1 (30)
Operating Range (RPM)	5300 - 6300
Steering	Tiller
Oil Pan Capacity liters (U.S. / Imp qts.)	1.5 (1.6)
Ignition System	Digital CDI
Alternator	Manual 12V 6A / Electric 12V 12A
Trim Method	Power Trim & Tilt  Gas Assist
Gear Ratio	2.09:1
Gear Shift	F-N-R
Exhaust	Through Prop Hub Exhaust
Propeller Selection (in.)	10-14
Fuel Tank Capacity	Separate 25L

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

**FOR YOUR SAFETY:**

- Read your owner's manual carefully.
- Operate your outboard safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts