



DF350A

Specifications & Advantages

Engine Type	V6 - 55° DOHC 24-Valve	
Fuel Delivery System	Electronic Fuel Injection	
Transom Height mm (in.)	X: 635 (25)	XX: 762 (30)
Starting System	Electric	
Dry Weight kg (lbs.):	X: 330 (727)	XX: 339 (747)
No. Of Cylinders	6	
Piston Displacement cc (cu. in.)	4,390 (267.9)	
Bore X Stroke Inches (mm)	98 (3.74) x 97 (3.82)	
Maximum Output Kw (HP) / RPM	257.4 (350)	
Operating Range (RPM)	5,700 - 6,300	
Steering	Remote	
Oil Pan Capacity liters (U.S. / Imp qts.)	8.0 (8.5)	
Ignition System	Fully-transistorized	
Alternator	12V 54A	
Trim Method	Power Trim and Tilt	
Gear Ratio	2.29:1	
Gear Shift	F-N-R (Drive-by-Wire)	
Exhaust	Through Prop Hub Exhaust	
PROPELLER SELECTION (Pitch)	FRONT: 3×15 1/2×19.5-31.5 REAR: 3×15 1/2×19.5-31.5	
All propellers are the 3-blade type		

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner's manual carefully.
- Operate your outboard safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts