

GSX-S1000 ABS

SPECIFICATIONS

Engine:	999cc, 4-stroke, liquid-cooled, 4-cylinder, DOHC
Bore Stroke:	73.4 x 59.0 mm (2.890 x 2.323 in.)
Compression Ratio:	12.2 : 1
Fuel System:	Suzuki Fuel Injection with SDTV
Lubrication:	Wet Sump
Ignition:	Electronic ignition (Transistorized)
Transmission:	6-speed constant mesh
Final Drive:	Chain, RK525GSH, 116 links
Overall Length:	2115 mm (83.3 in)
Overall Width:	795 mm (31.3 in)
Seat Height:	810 mm (31.9 in)
Ground Clearance:	140 mm (5.5 in)
Wheelbase:	1460 mm (57.5 in)
Curb Weight:	214 kg (472 lb)
Suspension Front:	Inverted telescopic, coil spring, oil damped
Suspension Rear:	Link type, single shock, coil spring, oil damped
Brakes Front:	Brembo 4-piston, Disc, twin, ABS-equipped
Brakes Rear:	Nissin, 1-piston, Disc single, ABS-equipped
Tires Front:	120/70ZR17M/C (58W), tubeless
Tires Rear:	190/50ZR17M/C (73W), tubeless
Fuel Tank Capacity:	17.0 L (4.5 US gallons)
Color:	Metallic Triton Blue/Glass Sparkle Black

Specifications, appearances, equipment, colors, materials and other items of “SUZUKI” products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner’s manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts