

## GSX-S1000Z ABS

### SPECIFICATIONS

<b>Engine:</b>	999cc, 4-stroke, liquid-cooled, 4-cylinder, DOHC
<b>Bore Stroke:</b>	73.4 x 59.0 mm (2.890 x 2.323 in.)
<b>Compression Ratio:</b>	12.2 : 1
<b>Fuel System:</b>	Suzuki Fuel Injection with SDTV
<b>Lubrication:</b>	Wet Sump
<b>Ignition:</b>	Electronic ignition (Transistorized)
<b>Transmission:</b>	6-speed constant mesh
<b>Final Drive:</b>	Chain, RK525GSH, 116 links
<b>Overall Length:</b>	2115 mm (83.3 in)
<b>Overall Width:</b>	795 mm (31.3 in)
<b>Seat Height:</b>	810 mm (31.9 in)
<b>Ground Clearance:</b>	140 mm (5.5 in)
<b>Wheelbase:</b>	1460 mm (57.5 in)
<b>Curb Weight:</b>	214 kg (472 lb)
<b>Suspension Front:</b>	Inverted telescopic, coil spring, oil damped
<b>Suspension Rear:</b>	Link type, single shock, coil spring, oil damped
<b>Traction Control:</b>	ABS
<b>Brakes Front:</b>	Brembo 4-piston, Disc, twin, ABS-equipped
<b>Brakes Rear:</b>	Nissin, 1-piston, Disc single, ABS-equipped
<b>Tires Front:</b>	120/70ZR17M/C (58W), tubeless
<b>Tires Rear:</b>	190/50ZR17M/C (73W), tubeless
<b>Fuel Tank Capacity:</b>	17.0 L (4.5 US gallons)
<b>Color:</b>	Metallic Mat Black No. 2

Specifications, appearances, equipment, colors, materials and other items of “SUZUKI” products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

#### FOR YOUR SAFETY:

- Read your owner’s manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts