

GSX-S750

SPECIFICATIONS

Engine:	749 cc, 4-stroke, liquid-cooled, 4-cylinder, DOHC
Bore Stroke:	72.0 mm (2.83 in) x 46.0 mm (1.81 in)
Compression Ratio:	12.3 : 1
Fuel System:	Suzuki Fuel Injection with SDTV
Lubrication:	Wet Sump
Ignition:	Electronic ignition (Transistorized)
Transmission:	6-speed constant mesh
Final Drive:	Chain, RK525GSH, 116 links
Overall Length:	2125 mm (83.6 in.)
Overall Width:	785 mm (30.9 in)
Seat Height:	820 mm (32.2 in.)
Ground Clearance:	135 mm (5.3 in.)
Wheelbase:	1455 mm (57.2 in.)
Curb Weight:	211 kg (465 lbs.)
Suspension Front:	Inverted telescopic, coil spring, oil damped
Suspension Rear:	Link type, single shock, coil spring, oil damped
Brakes Front:	Nissin, 4-piston, Disc, twin
Brakes Rear:	Nissin, 1-piston, Disc single
Tires Front:	120/70ZR17M/C (58W), tubeless
Tires Rear:	190/50ZR17M/C (73W), tubeless
Fuel Tank Capacity:	16.0 L (4.22 US gallons)
Color:	Metallic Triton Blue / Glass Sparkle Black and Pearl Mira Red

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner's manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts