

2018 King Quad / LT-A750Xi

SPECIFICATIONS

Engine:	722cc (44.1 cu. in), 4-stroke, liquid-cooled, DOHC
Bore Stroke:	104.0 mm (4.094 in) x 85.0 mm (3.346 in)
Compression Ratio:	10.0 : 1
Fuel System:	Fuel injection
Lubrication:	Wet sump
Ignition:	Electronic ignition (CDI)
Transmission:	CVT (V-belt), with high-/low-range, and reverse
Final Drive:	Shaft drive
Overall Length:	2115 mm (83.3 in)
Overall Width:	1210 mm (47.6 in)
Overall Height:	1245 mm (49.0 in)
Seat Height:	880 mm (34.6 in)
Ground Clearance:	270 mm (10.6 in)
Wheelbase:	1280 mm (50.4 in)
Curb Weight:	302 kg (665 lbs)
Suspension Front:	Independent, double wishbone, coil spring, oil damped
Suspension Rear:	Independent, double wishbone, coil spring, oil damped
Brakes Front:	Disc brake, twin
Brakes Rear:	Sealed oil-bathed multi-disc
Tires Front:	AT25 × 8-12, tubeless
Tires Rear:	AT25 × 10-12, tubeless
Fuel Tank Capacity:	17.5 L (4.6/3.8 US/Imp gal)
Color:	Terra Green and Flame Red

Specifications, appearances, equipment, colors, materials and other items of “SUZUKI” products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- The LT-A750X is for use only by those aged 16 and older.
- Read your owner’s manual carefully.
- Follow all scheduled maintenance as recommended.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- ATVs can be hazardous to operate.
- Always avoid paved surfaces. Never ride on public roads.
- Never carry passengers or engage in stunt riding.
- Avoid excessive speed. Be extra careful on difficult terrain.