



Boulevard C50T

Engine:	805 cc (49.1 cu. in), 4-stroke, Liquid-cooled, OHC, 45 V-twin
Bore Stroke:	83.0 mm (3.268 in) x 74.4 mm (2.929 in)
Compression Ratio:	9.4 : 1
Fuel System:	Fuel injection
Lubrication:	Wet sump
Ignition:	Electronic ignition (Transistorized)
Transmission:	5-speed constant mesh
Final Drive:	Shaft Drive
Overall Length:	2500 mm (98.4 in)
Overall Width:	955 mm (37.6 in)
Overall Height:	1110 mm (43.7 in)
Seat Height:	700 mm (27.6 in)
Ground Clearance:	140 mm (5.5 in)
Wheelbase:	1655 mm (65.2 in)
Curb Weight:	277 kg (611 lbs)
Suspension Front:	Telescopic, coil spring, oil damped
Suspension Rear:	Link type, coil spring, oil damped
Brakes Front:	Disc brake
Brakes Rear:	Drum brake
Tires Front:	130/90-16M/C 67H, tubeless
Tires Rear:	170/80-15M/C 77H, tubeless
Fuel Tank Capacity:	15.5 L (4.1/3.4 US/Imp gal)
Color:	Glass Sparkle Black

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner's manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts