

DL1000A/ V-STROM

SPECIFICATIONS

Engine:	1037cc, 4-stroke, 2-cylinder, liquid-cooled, DOHC, 90-degree V-Twin
Bore Stroke:	100.0 mm x 66.0 mm (3.937 in x 2.598 in)
Compression Ratio:	11.3 : 1
Fuel System:	Suzuki Fuel Injection
Lubrication:	Wet sump
Ignition:	Electronic ignition (CDI)
Transmission:	6-speed, constant mesh
Final Drive:	Chain
Overall Length:	2280 mm (89.8 in.)
Overall Width:	930 mm (36.6 in.)
Seat Height:	850mm (33.4in)
Ground Clearance:	165 mm (6.5 in)
Wheelbase:	1555 mm (61.22 in)
Curb Weight:	232 kg (511 lbs.)
Suspension Front:	Inverted telescopic, coil spring, oil damped
Suspension Rear:	Link type, coil spring, oil damped
Brakes Front:	Tokico 4-piston calipers, Disc, twin
Brakes Rear:	Nissin, 2-piston, Disc single
Tires Front:	110/80R19M/C 59V, tubeless
Tires Rear:	150/70R17M/C 69V, tubeless
Fuel Tank Capacity:	20.0 L (5.3 US gallons)
Color:	Pearl Glacier White

Specifications, appearances, equipment, colors, materials and other items of “SUZUKI” products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner’s manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts