



Way of Life!

DL650A/ V-STROM

SPECIFICATIONS

Engine:	645 cc, 4-stroke, 2-cylinder, liquid-cooled, DOHC, 90-degree V-Twin
Bore Stroke:	81.0 mm x 62.6 mm (3.189 in x 2.465 in)
Compression Ratio:	11.2 : 1
Fuel System:	Suzuki Fuel Injection
Lubrication:	Wet sump
Ignition:	Electronic ignition (CDI)
Transmission:	6-speed, constant mesh
Final Drive:	Chain, DID525V8, 118 links
Overall Length:	2290 mm (90.2 in)
Overall Width:	835 mm (32.9 in)
Seat Height:	835 mm (32.9 in)
Ground Clearance:	175 mm (6.9 in)
Wheelbase:	1560 mm (61.4 in)
Curb Weight:	214 kg (472 lbs)
Suspension Front:	Inverted telescopic, coil spring, oil damped
Suspension Rear:	Link type, coil spring, oil damped
Brakes Front:	Disc, twin
Brakes Rear:	Disc brake
Tires Front:	110/80R19M/C 59H, tubeless
Tires Rear:	150/70R17M/C 69H, tubeless
Fuel Tank Capacity:	5.3 US
Color:	Pearl Bracing White, Candy Daring Red

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner's manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts