

DR-Z400SM

SPECIFICATIONS

Engine:	398cc, 4-stroke, liquid-cooled, single cylinder, DOHC
Bore Stroke:	90.0 mm (3.543 in) x 62.6 mm (2.465 in)
Compression Ratio:	11.3 : 1
Fuel System:	MIKUNI BSR36, single
Lubrication:	Dry sump
Ignition:	Electronic ignition (CDI)
Transmission:	5-speed constant mesh
Final Drive:	RK520KZO, 110 links
Overall Length:	2225 mm (87.6 in)
Overall Width:	855 mm (33.7 in)
Overall Height:	1200 mm (47.2 in)
Seat Height:	890 mm (35.0 in)
Ground Clearance:	260 mm (10.2 in)
Wheelbase:	1460 mm (57.5 in)
Curb Weight:	146 kg (321 lbs)
Suspension Front:	Inverted telescopic, coil spring, oil damped
Suspension Rear:	Link type, coil spring, oil damped
Brakes Front:	Disc brake, single floating rotor
Brakes Rear:	Disc brake, single rotor
Tires Front:	120/70R17M/C 58H, tube type
Tires Rear:	140/70R17M/C 66H, tube type
Fuel Tank Capacity:	10.0 L (2.6/2.2 US/Imp gal) - Including Reserve (CA: 9.5 L (2.5/2.1 US/Imp gal) -Including Reserve)
Color:	Solid Black

Specifications, appearances, equipment, colors, materials and other items of “SUZUKI” products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner’s manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts