

GSXR1300RA

SPECIFICATIONS

Engine:	1340 cc (81.8 cu.in), 4-stroke, liquid-cooled, DOHC
Bore Stroke:	81.0 mm (3.189 in) x 65.0 mm (2.559 in)
Compression Ratio:	12.5:1
Fuel System:	Fuel injection
Lubrication:	Wet Sump
Ignition:	Electronic ignition (Transistorized)
Transmission:	6-speed constant mesh
Final Drive:	RK GB50GSV Z4, 114 links
Overall Length:	2190 mm (86.2 in)
Overall Width:	735 mm (28.9 in)
Overall Height:	1165 mm (45.9 in)
Seat Height:	805 mm (31.7 in)
Ground Clearance:	120 mm (4.7 in)
Wheelbase:	1480 mm (58.3 in)
Curb Weight:	260 kg (573 lbs)
Suspension Front:	Inverted telescopic, coil spring, oil damped
Suspension Rear:	Linky type, coil spring, oil damped
Brakes Front:	Brembo, Disc, twin
Brakes Rear:	Disc brake
Tires Front:	120/70ZR17M/C (58W), tubeless
Tires Rear:	190/50ZR17M/C (73W), tubeless
Fuel Tank Capacity:	21.0 L (5.5/4.6 US/Imp gal)
Color:	Pearl Mira Red /Pearl Glacier White

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner's manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts