

# 2018 GSX250R

## SPECIFICATIONS

<b>Engine:</b>	Four-stroke, liquid-cooled, SOHC, parallel-twin
<b>Displacement:</b>	248 cm <sup>3</sup> (15.13 cubic in.)
<b>Bore Stroke:</b>	53.5 x 55.2 mm (2.10 x 2.17 in.)
<b>Compression Ratio:</b>	11.5: 1
<b>Fuel System:</b>	Fuel Injection
<b>Lubrication:</b>	Wet sump
<b>Ignition:</b>	Electronic ignition (Transistorized)
<b>Transmission:</b>	6-speed, constant mesh
<b>Final Drive:</b>	Chain, Sealed O-ring type
<b>Overall Length:</b>	82.08 in. (2,085 mm)
<b>Overall Width:</b>	29.13 in. (740 mm)
<b>Overall Height:</b>	43.7 in. (1,110 mm)
<b>Seat Height:</b>	31.1 in. (790 mm)
<b>Ground Clearance:</b>	6.29 in. (160 mm)
<b>Wheelbase:</b>	56.29 in. (1,430 mm)
<b>Curb Weight:</b>	392.4 lbs. (178 kg.)
<b>Suspension Front:</b>	Telescopic, coil spring, oil damped
<b>Suspension Rear:</b>	Single shock, coil spring, oil damped
<b>Brakes Front:</b>	Single disc, Nissin 2-piston caliper
<b>Brakes Rear:</b>	Single-disc, Nissin 1-piston caliper
<b>Tires Front:</b>	110/80-17M/C 57H tubeless
<b>Tires Rear:</b>	140/55-17M/C 66H tubeless
<b>Fuel Tank Capacity:</b>	4.0 US gal. (15 L)
<b>Color:</b>	Pearl Glacier White No. 2, Pearl Nebular Black

Specifications, appearances, equipment, colors, materials and other items of “SUZUKI” products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

### FOR YOUR SAFETY:

- Read your owner’s manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts