

GSX-R1000

SPECIFICATIONS

Engine:	999.8 cc, 4-stroke, 4-cylinder, liquid-cooled, DOHC
Bore Stroke:	76.0 x 55.1 mm (2.992 x 2.169 in.)
Compression Ratio:	13.2 : 1
Fuel System:	Suzuki Fuel Injection with Ride-by-Wire 46mm throttle bodies
Lubrication:	Wet sump
Ignition:	Electronic ignition (Transistorized)
Transmission:	6-speed, constant mesh, cassette-style
Final Drive:	Chain drive, #525
Overall Length:	2075 mm (81.7 in.)
Overall Width:	705 mm (27.8 in.)
Overall Height:	1145 mm (45.1 in.)
Seat Height:	825 mm (32.5 in.)
Ground Clearance:	130 mm (5.1 in.)
Wheelbase:	1405mm (55.3 in.)
Curb Weight:	203 kg (448 lbs.)
Suspension Front:	SHOWA BFF, Inverted telescopic, coil spring, oil damped
Suspension Rear:	SHOWA BFF-Lite Shock, Link type, coil spring, oil damped
Brakes Front:	Brembo, Disc, Brembo 4-piston, Disc, twin, ABS-equipped
Brakes Rear:	Nissin, 1-piston, Disc single, ABS-equipped
Tires Front:	Bridgestone RS10, 120/70ZR17M/C (58W), tubeless
Tires Rear:	Bridgestone RS10, 190/55ZR17M/C (73W), tubeless
Fuel Tank Capacity:	16 L (4.2 US gal.)
Color:	Glass Sparkle Black and Metallic Triton Blue

Specifications, appearances, equipment, colors, materials and other items of "SUZUKI" products are subject to change by manufacturer at any time without previous notice and they may vary depending on local conditions or requirements.

Some models are not available in some territories. Each model might be discontinued without notice.

Please inquire at your local dealer for details of any such changes.

FOR YOUR SAFETY:

- Read your owner's manual carefully.
- Always wear a helmet, eye protection and protective clothing.
- Never ride under the influence of alcohol or other drugs.
- Operate your motorcycle safely and responsibly.
- Follow all scheduled maintenance as recommended.
- Use only SUZUKI Genuine Parts